



AGRICULTURAL TIRES

petlas
TRACK OF TRUST



Premium Quality Agricultural Tires

DESCRIPTION

* For load capacity and inflation pressure figures on different speed rates, please consult the producer company.

**Load capacity on standard speed and standard load.

Our company is entitled to change any information in this catalogue without prior notice.

This catalogue overrides any previous catalogues

All figures are for reference; our company cannot be deemed responsible for printing errors.

***The visual content of the catalogue is only representative. To find the compatible tire for your car, please refer to the car service or authorized dealer.

RANGE OF PETLAS AGRICULTURAL TIRES

Tractor Front



TD 16



TD 17



TD 18



TP 8



TD 25



TD 35



TA 50



TA 60

Tractor Rear



TA 60



TZ 13



TA 300



TA 330

Tractor Radial



TA 110



TA 120
ROW CROP



TA 130



TA 130
IF Series



TA 140

Trailer / Implement



TA 60



VF HLT 45



NT 3



NT 30



PA 20



NB 27



NB 37



UN 1 (3 RIB)



UN 1 (5 RIB)



UN 3



UN 5



UN 7



UN 9



UN 11



STB 3

Radial Harvester / Harvester



TA 130
AGROPER



PB 140
AGROPER



UN 9



BD 60



BD 65



TA 330



UN 1 (5 RIB)

Flotation / Forestry



IMF 18



IMT 18



IMT 08



TD 16

Front tire for 2WD tractors appropriate for using on field and short distance road operations.

Offers long life thanks to its wear-resistant tread compound. Durable shoulders protect the tire effectively by increasing its resistance to any kind of damage. Special tread design keeps the tread free of mud.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
5.50-16	6PR	TT	86/A6
6.00-16	6PR	TT	88/A6
6.50-16	6PR	TT	91/A6
6.50-16	8PR	TT	97/A6
7.50-16	6PR	TT	98/A6
7.50-16	8PR	TT	103/A6
6.00-19	6PR	TT	93/A6
6.50-20	8PR	TT	108/A6
6.50-20	10PR	TT	115/A6
7.50-20	8PR	TT	108/A6
7.50-20	10PR	TT	115/A6



TD 17

Ideal 2WD tractor front tire with special 3Rib design.

The rib design provides ultimate steering performance during soil tillage operations and on soft and cultivated areas. Specially formulated tread compound and all steel carcass structure offer longevity. Flexible carcass structure prevents sinking. Special tread design provides efficient self-cleaning feature.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
6.00-16	6PR	TT	88/A6
7.50-16	8PR	TT	103/A6
9.00-16	8PR	TT	111/A6
11.00-16	8PR	TT	118/A6



TD 18

Front tire for 2WD tractors suitable to be used on field and short distance road operations.

Improved tread compound enable high resistance against wears and cuts. Strong center and shoulder design improves durability towards side impacts and tread base fatigue. Tread pattern and flexible carcass structure provide excellent maneuverability without sinking into the soil. Special tread geometry provides easy steering.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
6.50-16	6PR	TT	91/A6
6.50-16	8PR	TT	97/A6
7.50-18	8PR	TT	106/A6
7.50-20	8PR	TT	108/A6



TP 8

Front tire for 2WD tractors suitable to be used on field and short distance road operations.

Improved tread compound enable high resistance against wears and cuts. Strong center and shoulder design provides high resistance to side impacts and tread base fatigue. Tread pattern and flexible carcass structure provide excellent maneuverability without sinking into the soil. Special tread geometry provides easy steering.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
6.00-16	6PR	TT	88/A6
7.50-16	8PR	TT	103/A6



TD 25

Front tire for 2WD tractors suitable to be used on field and short distance road operations.

Solid tread center structure and strong nylon carcass enhances durability. Durable shoulders protect the tire effectively by increasing its resistance to any kind of damage. The strong and flexible carcass structure that prevents sinking into the soil also ensures long life.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
6.00-16	6PR	TT	88/A6
6.00-16	10PR	TT	98/A6
6.50-16	6PR	TT	91/A6
6.50-16	8PR	TT	97/A6
7.50-16	8PR	TT	103/A6



TD 35

Ideal 2WD tractor front tire with special 3Rib design.

The rib design provides ultimate steering performance during soil tillage operations and on soft and cultivated areas. Specially formulated tread compound and all steel carcass structure offer longevity. Flexible carcass structure prevents sinking into the soil. Special tread design provides efficient self-cleaning feature.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
10.00-16	8PR	TT	114/A6



TA 50

High traction R1 tractor front tire for medium and low powered tractors.

Wide and strong body provides easy grip and high traction. Tread profile provides outstanding durability to tread base fatigue. Highly resistant to cuts and wears. Offers effective self-cleaning feature and grip performance during tillage operations by its special tread geometry.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
6.5/80-12	6PR	TL	80/A6
6.5/80-13	6PR	TT	94/A6



TA 60

High traction R1 tractor front tire for medium and low powered tractors.

Offers long service life thanks to its wear resistant tread compound. Tread profile enables high resistance to tread base fatigue. The wide and long lugs provide comfortable drive while improving grip performance. Wide and strong body ensures ultimate grip and high traction. Special tread geometry offers efficient self-cleaning feature.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
5.00-10	4PR	TT	70/58/A6
5.00-12	4PR	TT	62/A6
6.5/80-12	6PR	TT	80/A6
7.00-12	6PR	TT	83/A6
10.0/80-12	6PR	TT/TL	98/A6
5.00-15	6PR	TT	88/A6
6.00-16	6PR	TT	88/A6
6.50-16	6PR	TT	91/A6
7.50-16	8PR	TT	103/A6
7.00-18	8PR	TT	106/A6
7.50-18	8PR	TT	106/A6
7.50-20	8PR	TT	108/A6
8.00-20	8PR	TT	113/A6
9.50-20	8PR	TT	107/A6

TA 60

High traction R1 tractor rear tire for medium and low powered tractors.

The wide and long lugs provide comfortable drive while improving grip performance. Offers long service life thanks to its wear resistant tread compound. Wide and strong body provides ultimate grip and high traction. Tread profile enables high resistance to tread base fatigue. Special tread geometry provides efficient self-cleaning feature.



TYRE SIZE	PR	TT/TL	LOAD SPEED INDEX	TYRE SIZE	PR	TT/TL	LOAD SPEED INDEX
8.3-24	8PR	TT	108/A6	16.9/14-30	14PR	TT	144/A6
9.5-24	8PR	TT	112/A6	18.4/15-30	6PR	TT	134/A6
11.2-24	8PR	TT	116/A6	18.4/15-30	8PR	TT	139/A6
11.2-28	8PR	TT	118/A6	18.4/15-30	10PR	TT	145/A6
14.9/13-24*	8PR	TT	128/A6	18.4/15-30	12PR	TT	149/A6
14.9/13-24	4PR	TL	112/A6	18.4/15-30	14PR	TT	151/A6
14.9/13-24	4PR	TT	112/A6	12.4/11-32	8PR	TT	124/A6
14.9/13-24	6PR	TT	123/A6	16.9/14-34	8PR	TT	139/A6
14.9/13-24	8PR	TT	128/A6	16.9/14-34	10PR	TT	142/A6
14.9/13-24	10PR	TT	134/A6	16.9/14-34	12PR	TT	145/A6
14.9/13-24	14PR	TT	142/A6	16.9/14-34	14PR	TT	148/A6
12.4/11-24	6PR	TT	115/A6	18.4/15-34	8PR	TT	141/A6
12.4/11-24	8PR	TT	120/A6	18.4/15-34	10PR	TT	146/A6
12.4/11-24	12PR	TT	128/A6	18.4/15-34	12PR	TT	151/A6
13.6/12-24	8PR	TT	123/A6	18.4/15-34	14PR	TT	156/A6
18.4/15-26	12PR	TT	146/A6	12.4/11-36	8PR	TT	126/A6
18.4/15-26	14PR	TT	149/A6	12.4/11-36	14PR	TT	139/A6
18.4/15-26	12PR	TL	146/A6	13.6/12-36	6PR	TT	125/A6
12.4/11-28	6PR	TT	117/A6	13.6/12-36	8PR	TT	129/A6
12.4/11-28	8PR	TT	122/A6	13.6/12-38	8PR	TT	131/A6
13.6/12-28	6PR	TT	121/A6	13.6/12-38	14PR	TT	142/A6
13.6/12-28	8PR	TT	125/A6	14.00-38	8PR	TT	131/A6
14.9/13-28	6PR	TT	125/A6	14.00-38	10PR	TT	136/A6
14.9/13-28	8PR	TT	130/A6	15.5-38	8PR	TT	133/A6
16.9/14-28	8PR	TT	135/A6	15.5-38	10PR	TT	138/A6
16.9/14-28	10PR	TT	139/A6	15.5-38	12PR	TT	142/A6
16.9/14-28	12PR	TT	143/A6	15.5-38	14PR	TT	145/A6
14.9/13-30	8PR	TT	131/A6	16.9/14-38	8PR	TT	141/A6
14.9/13-30	10PR	TT	135/A6	16.9/14-38	10PR	TT	144/A6
16.9/14-30	8PR	TT	137/A6	16.9/14-38	12PR	TT	142/A6
16.9/14-30	10PR	TT	139/A6	18.4-38	8PR	TT	143/A6
16.9/14-30	12PR	TT	143/A6	18.4-38	10PR	TT	147/A6

* IRRIGATION TIRE

TZ 13

Tractor rear tire for field operations.

Strong nylon carcass structure provides optimum durability. Resistant to cuts and wears thanks to its special compound. High lugs provide excellent traction at all operating conditions. Offers safe handling on steep or hilly grounds.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
12.4/11-28	8PR	TT	122/A6
16.9/14-30	10PR	TT	139/A6
16.9/14-30	12PR	TT	144/A6



TA 300

R1 tractor rear tire.

Special lug design provides maximum traction while simultaneously offering excellent self-cleaning feature. Strong nylon carcass structure provides optimum durability. Open center pattern ensures high resistance to tread base fatigue. Resistant to cuts and wears thanks to its special compound. Ensures handling stability on steep or hilly grounds.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
9.5-24	8PR	TT	112/A6
11.2-24	8PR	TT	116/A6
14.9/13-24	8PR	TT	128/A6
12.4/11-24	8PR	TT	120/A6
12.4/11-24	10PR	TT	124/A6
13.6/12-24	8PR	TT	123/A6
12.4/11-28	8PR	TT	122/A6
13.6/12-28	8PR	TT	125/A6
14.9/13-28	8PR	TT	130/A6
14.9/13-30	8PR	TT	131/A6
16.9/14-30	10PR	TT	139/A6
16.9/14-34	8PR	TT	139/A6
18.4/15-30	8PR	TT	139/A6
18.4/15-30	10PR	TT	145/A6
18.4/15-30	12PR	TT	149/A6
18.4/15-30	14PR	TT	151/A6
18.4/15-34	8PR	TT	141/A6
12.4/11-36	8PR	TT	126/A6
13.6/12-36	8PR	TT	129/A6
16.9/14-38	8PR	TT	141/A6

TA 330

R1 tractor rear tire.

Provides superior performance on tough terrains with its specially designed tread pattern. The unique lug design prevents any kind of crop damage and provides easy cleaning feature during field operations. Wide and reinforced body provides perfect grip, high traction and reduced slippage. Exceptional carcass structure provides optimum durability. Tread profile with extra wide tread base ensures perfect resistance to tread base fatigue.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
30.5L-32	12PR	TL	158/A8



TA 110

General purpose R-1W tractor radial tire.

Wider footprint offers lower soil compaction. Special structure improves flotation on soft terrains and ensures a comfortable ride at all operating conditions. Low rolling resistance leads to maximum fuel efficiency. Unique tread design provides exceptional traction and ensures maximum performance. Special tread compound provides high level of resistance against wear and cuts. Tread profile enhances durability to tread base fatigue. Offers excellent self-cleaning feature.



TYRE SIZE	TT/TL	LOAD/SPEED INDEX
9.5 R20	TL	108/A8 105/B
280/85 R20 (11.2 R20)	TL	112/A8 109/B
320/85 R20 (12.4 R20)	TL	119/A8 116/B
9.5 R24	TL	107/A8 104/B
280/85 R24 (11.2 R24)	TL	115/A8 112/B
320/85 R24 (12.4 R24)	TL	122/A8 119/B
340/85 R24 (13.6 R24)	TL	125/A8 122/B
380/85 R24 (14.9 R24)	TL	131/A8 128/B
420/85 R24 (16.9 R24)	TL	137/A8 134/B
280/85 R28 (11.2 R28)	TL	118/A8 115/B
320/85 R28 (12.4 R28)	TL	124/A8 121/B
340/85 R28 (13.6 R28)	TL	127/A8 124/B
380/85 R28 (14.9 R28)	TL	133/A8 130/B
420/85 R28 (16.9 R28)	TL	139/A8 136/B
380/85 R30 (14.9 R30)	TL	135/A8 132/B
420/85 R30 (16.9 R30)	TL	140/A8 137/B
460/85 R30 (18.4 R30)	TL	145/A8 142/B
320/85 R32 (12.4 R32)	TL	126/A8
380/85 R34 (14.9 R34)	TL	137/A8 137/B
420/85 R34 (16.9 R34)	TL	142/A8 139/B
460/85 R34 (18.4 R34)	TL	147/A8 144/B
320/85 R36 (12.4 R36)	TL	128/A8 125/B
340/85 R36 (13.6 R36)	TL	132/A8 129/B
320/85 R38 (12.4 R38)	TL	143/A8 143/B
340/85 R38 (13.6 R38)	TL	133/A8 130/B
380/85 R38 (14.9 R38)	TL	139/A8 136/B
420/85 R38 (16.9 R38)	TL	144/A8 141/B
460/85 R38 (18.4 R38)	TL	149/A8 146/B
460/85 R38 (18.4 R38) RF	TL	149/A8 146/B
520/85 R38 (20.8 R38)	TL	155/A8 152/B
520/85 R38 (20.8 R38) RF	TL	155/A8 152/B

TRACTOR RADIAL

TYRE SIZE	TT/TL	LOAD/SPEED INDEX
520/85 R42 (20.8 R42)	TL	157/A8 157B
520/85 R42 (20.8 R42) RF	TL	162/A8
520/85 R46 (20.8 R46)	TL	158/A8 155/B
650/85 R38	TL	173/A8 173/B
260/80 R20 (8.00 R20)	TL	106/A8 103/B
480/80 R38 (18.4 R38)	TL	149/A8
480/80 R42 (18.4 R42)	TL	151/A8 148/B
480/80 R46 (18.4 R46)	TL	158/A8 158/B
480/80 R50 (18.4 R50)	TL	159/A8 159/B
200/70 R16	TL	94/A8
240/70 R16 (6.00 R16)	TL	104/A8 101/B
260/70 R16 (6.50 R16)	TL	109/A8 106/B
260/70 R20 (6.50 R20)	TL	113/A8 113/B
280/70 R16 (7.50 R16)	TL	112/A8 112/B
280/70 R18 (7.50 R18)	TL	114/A8 114/B
280/70 R20 (7.50 R20)	TL	116/A8 116/B
300/70 R20 (9.50 R20)	TL	110/A8 110/B
320/70 R20 (11.2 R20)	TL	113/A8 113/B
360/70 R20 (12.4 R20)	TL	120/A8 117/B
380/70 R20 (13.6 R20)	TL	132/A8
320/70 R24 (11.2 R24)	TL	116/A8 113/B
360/70 R24 (12.4 R24)	TL	122/A8 119/B
380/70 R24 (13.6 R24)	TL	125/A8 125/B
420/70 R24 (14.9 R24)	TL	130/A8 127/B
480/70 R24 (16.9 R24)	TL	138/A8 135/B
480/70 R26 (16.9 R26)	TL	139/A8 136/B
320/70 R28 (11.2 R28)	TL	119/A8 116/B
360/70 R28 (12.4 R28)	TL	125/A8 122/B
380/70 R28 (13.6 R28)	TL	127/A8 124/B
420/70 R28 (14.9 R28)	TL	133/A8 130/B
480/70 R28 (16.9 R28)	TL	140/A8 140/B
420/70 R30 (14.9 R30)	TL	134/A8 131/B
480/70 R30 (16.9 R30)	TL	141/A8 138/B
520/70 R30 (18.4 R30)	TL	145/A8 142/B
480/70 R34 (16.9 R34)	TL	143/A8 140/B
520/70 R34 (18.4 R34)	TL	148/A8 145/B
480/70 R38 (16.9 R38)	TL	145/A8 142/B
520/70 R38 (18.4 R38)	TL	150/A8 147/B
580/70 R38 (20.8 R38)	TL	155/A8 152/B
580/70 R42 (20.8 R42)	TL	158/A8
420/65 R24 (12.4 R24)	TL	126/D
440/65 R24 (13.6 R24)	TL	128/D 131/A8
440/65 R24 (13.6 R24)	TL	135/D 138/A8
480/65 R24 (14.9 R24)	TL	133/D 136/A8
480/65 R24 (14.9 R24)	TL	140/D 143/A8
540/65 R24 (16.9 R24)	TL	140/D 143/A8
540/65 R24 (16.9 R24)	TL	146/D 149/A8
440/65 R28 (13.6 R28)	TL	131/D 134/A8
440/65 R28 (13.6 R28)	TL	138/D 141/A8
480/65 R28 (14.9 R28)	TL	136/D 139/A8
480/65 R28 (14.9 R28)	TL	142/D 145/A8
540/65 R28 (16.9 R28)	TL	149/D 152/A8
540/65 R30 (16.9 R30)	TL	150/D 153/A8
540/65 R34 (16.9 R34)	TL	145/D 148/A8
540/65 R34 (16.9 R34)	TL	152/D 155/A8
540/65 R38 (16.9 R38)	TL	147/D 150/A8
540/65 R38 (16.9 R38)	TL	153/D 156/A8
600/65 R34 (18.4 R34)	TL	151/D 154/A8
600/65 R34 (18.4 R34)	TL	157/D 160/A8
600/65 R38 (18.4 R38)	TL	159/D 162/A8
650/65 R38	TL	163/D 166/A8

RF: REINFORCED



petlas

TA 120

General purpose R-1W row crop tractor and sprayer tire.

Narrow profile protects the crop from damages. Robust carcass structure enables maximum performance under heavy loads. Deep lugs and special tread compound ensure longevity. Special tread compound provides high resistance against wear and cuts. Tread design enhances self-cleaning capability and reduces slippage.



TYRE SIZE	TT/TL	LOAD/SPEED INDEX
210/95 R32 (8.3 R32)	TL	114/A8 114/B
210/95 R32 (8.3 R32)	TL	120/A8 120/B
230/95 R32 (9.5 R32)	TL	126/A8 126/B
270/95 R32 (11.2 R32)	TL	136/A8 136/B
210/95 R36 (8.3 R36)	TL	116/A8 116/B
230/95 R36 (9.5 R36)	TL	128/A8 128/B
270/95 R38 (11.2 R38)	TL	140/A8 140/B
230/95 R40 (9.5 R40)	TL	122/A8 122/B
210/95 R44 (8.3 R44)	TL	120/A8 120/B
230/95 R44 (9.5 R44)	TL	132/A8 132/B
270/95 R44 (11.2 R44)	TL	142/A8 142/B
300/95 R46 (12.4 R46)	TL	148/A8 148/B
230/95 R48 (9.5 R48)	TL	136/A2
270/95 R48 (11.2 R48)	TL	144/A8 144/B
270/95 R54 (11.2 R54)	TL	157/A2
300/95 R52 (12.4 R52)	TL	156/D
380/90 R46	TL	159/D
340/85 R48	TL	151/D



TA 130

R-1W tire for high power tractors.

Designed to transfer torque power to the ground effectively on any terrain. Special tread geometry reduces slippage by improving traction which in turn, leads to significant fuel savings. Wider footprint and optimized lug angle contributes to crop productivity by minimizing soil compaction. Elastic structure absorbs impacts and demonstrates better flotation. Strong carcass and high-quality tread compound ensure longer service life and enable maximum performance under heavy loads. Provides driving comfort both on the road and the field.



TYRE SIZE	TT/TL	LOAD/SPEED INDEX
600/70 R28	TL	161/D
600/70 R30 (23.1 R26)	TL	158/D
600/70 R34	TL	160/D
710/70 R38	TL	171/D
800/70 R38	TL	178/D
620/70 R42	TL	166/D
710/70 R42	TL	173/D
600/65 R28 (18.4 R28)	TL	154/D 157/A8
600/65 R42 (18.4 R42)	TL	154/D 157/A8
650/65 R42 (20.8 R42)	TL	170/D



TA 130 IF Series

R-1W tire for high power tractors.

Demonstrates superior performance under heavy loads with lower pressure compared to traditional radial tires. Lower inflation pressure and sidewall flexibility improves driving comfort. Special tread design provides exceptional traction. Highly flexible sidewalls and large footprint offer lower soil compaction. Elastic structure effectively protects the tire by absorbing impacts. Strong carcass and special tread compound ensure longer service life.



TYRE SIZE	TT/TL	LOAD/SPEED INDEX
600/70 R30	TL	165/D
800/70 R38	TL	184/D



TA 140

General purpose R-1W tractor front and rear tire.

Offers durability for a wide spectrum of applications. Special tread compound offers longevity by improving the tire resistance against wear and cuts. Wide footprint leads to lower soil compaction. Prevents slipping on all terrains and thus, contributes to steering balance. Elastic structure prevents sinking into the soil and protects the tire by absorbing impacts effectively.



TYRE SIZE

TT/TL

LOAD/SPEED INDEX

340/85 R28 (13.6 R28)

TL

127/A8 124/B



TA 60

General purpose trailer tire.

Offers long service life thanks to its wear resistant tread compound. Tread profile enables high resistance to tread base fatigue. The wide and long lugs provide comfortable drive while improving grip performance. Wide and strong body ensures ultimate grip and high traction. Special tread geometry offers efficient self-cleaning feature.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
10.0/75-15.3	12PR	TT	114/A6
11.5/80-15.3	12PR	TT	123/A6
11.5/80-15.3	12PR	TL	123/A6



VF HLT 45

Multipurpose VF (Very High Flexion) all steel radial tire designed hold up to heavier loads.

Thanks to VF (Very High Flexion) technology, carries more load with equal pressure levels and same load with less pressure when compared to conventional tires. Tread compound provides resistance to cuts and wears on asphalt, hard soil and concrete roads. Wide footprint provides lower soil compaction. Protects crops effectively with the help of its high flexion feature. Special carcass structure offers high endurance against stubble impacts and fissures.



TYRE SIZE

TT/TL

LOAD/SPEED INDEX

VF 285/70 R19.5

TL

152/D



NT 3

Traction type trailer tire with high resistance.

Suitable for transport and soil tillage operations. Special tread and carcass structure offers high load capacity. Wide and deeper tread design provides high resistance against cuts and tread fatigue.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
9.00-16	12PR	TL	125/A6
9.00-16	12PR	TT	125/A6
9.00-16	14PR	TT	128/A6
9.00-16	16PR	TT	131/A6
11.5/80-15.3	16PR	TL	141/A8



NT 30

Flexible and durable trailer tire.

Special tread and carcass structure offers high load capacity on soft surfaces. Offers high resistance against cuts and stubble puncture thanks to its specially developed tread compound and geometry. Flexible carcass structure prevents sinking into the soil while protecting the tire by absorbing impacts.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
9.00-16	12PR	TT	125/A6
9.00-16	14PR	TT	128/A6
9.00-16	16PR	TT	131/A6



PA 20

Traction type trailer tire.

Suitable for short period transport along with field use. Special tread and carcass structure offer high load capacity. Offers high resistance against lug fatigue and tread wear thanks to its specially developed tread compound and geometry.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
8.25-20	14PR	TT	133/A6



NB 27

Traction type trailer tire.

Special tread and carcass structure offers high load capacity. Flexible carcass structure prevents sinking into the soil while protecting the tire by absorbing side impacts. Offers high resistance against lug fatigue and tread wear thanks to its specially developed tread compound and geometry.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
9.00-20	14PR	TT	133/A6



NB 37

Traction type trailer tire with high resistance.

Reinforced sidewalls provide durability and protect the tire from side impacts. Special tread depth and geometry offers high resistance to cuts and tread wear. Offers high load capacity and outstanding self-cleaning feature.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
7.50-16	12PR	TT	121/A6



UN1 (3 RIB)

The ideal trailer tire for high load capacity with minimum soil compaction.

Offers high loading capacity with minimum soil compaction thanks to special three-rib tread design. Reinforced carcass structure ensures longevity by improving resistance against cuts and wears. Offers excellent self-cleaning features.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
7.50-16	10PR	TT	116/A6



UN 1 (5 RIB)

Modern harvester and trailer tire.

Demonstrates low dynamic rotating resistance thanks to its 5 Rib design. Suitable for short period transport and field use. Wide base area prevents slides to sides and sinking into the soil. Special tread design and structure ensures high resistance against cuts and wears.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
10.5/65-16	10PR	TT	123/A8
340/55-16	12PR	TL	140/A8
10.5/80-18	14PR	TT	142/A8
12.5/80-18	14PR	TT	146/A8
13.0/65-18	14PR	TT	141/A8
10.0/75-15.3	10PR	TT	123/A8
10.0/75-15.3	14PR	TL	130/A8
11.5/80-15.3	12PR	TT	135/A6
11.5/80-15.3	12PR	TL	135/A8
11.5/80-15.3	14PR	TL	139/A8
12.5/80-15.3	12PR	TL	139/A8
12.5/80-15.3	16PR	TL	144/A8
400/60-15.5	14PR	TL	145/A8
400/60-15.5	16PR	TL	147/A8
15.0/55-17	14PR	TL	137/A8
19.0/45-17	12PR	TL	141/A8
500/50-17	14PR	TL	149/A8
10.0/75-15.3	10PR	TL	123/A8
10.0/75-15.3	12PR	TL	126/A8
11.5/80-15.3	12PR	TL	135/A8
12.5/80-15.3	12PR	TL	139/A8

UN 3

General purpose trailer tire.

Provides high traction and leads to less soil compaction with its wide base area. Ensures perfect balance on soft terrains by preventing slide to sides. Offers resistance against cuts and wear with specially designed tread geometry. Special tread and carcass structure offers high load capacity.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
10.0/75-15.3	12PR	TL	126/A8
260/70-15.3	12PR	TL	126/A8
11.5/80-15.3	12PR	TL	137/A8
12.5/80-15.3	12PR	TL	141/A8



UN 5

General purpose trailer tire.

Special tread and carcass structure offers high load capacity. Minimizes soil compaction with its wide base area, providing high traction on soft terrains. Ensures perfect balance on soft surfaces by preventing slides to sides. Offers high resistance against cuts and tread wear with unique tread geometry.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
10.0/80-12	10PR	TT	122/A8
10.0/80-12	10PR	TL	122/A8



UN 7

Trailer tire designed for free rolling axle.

Special Low Section Height profile design ensures high performance. Wide tread design provides high flotation capability. Offers heavy load capacity and long service life with its durable carcass structure design. Special tread compound provides outstanding resistance against stubble punctures and cuts.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
9.5L-14SL	8PR	TL	111/B
9.5L-15SL	8PR	TT	112/B
9.5L-15SL	8PR	TL	112/B
9.5L-15SL	12PR	TL	121/B
11L-15SL	8PR	TL	113/B
11L-15SL	12PR	TL	121/B
12.5L-15SL	12PR	TL	127/B



UN 9

Trailer tire.

Stable central tread section with open shoulder design enhances comfort and improves longevity. Low rolling resistance leads to maximum efficiency in fuel consumption. Strong sidewall construction and durable bead structure provides excellent protection against all kinds of damage. Offers excellent floatation and self-cleaning features.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
16.0/70-20	14PR	TL	154/A8 142/A8
400/70-20	14PR	TL	154/A8 142/A8



UN 11

Free rolling tire designed to use on agricultural trailers and balers.

Delivers outstanding durability feature even under low air pressure and heavy load with its strong carcass structure. Protect crops with low soil compaction feature. Offers excellent flotation as rounded shoulders and wider base spread load on the surface. Enables driving comfort and fuel efficiency. Delivers excellent self-cleaning capability thanks to its wide grooves.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
500/50-17	16PR	TL	152/A8 139/A8
500/50-17	18PR	TL	157/A8 145/A8



STB 3

Trailer tire designed for free rolling axle.

Special tread compound provides excellent resistance against stubble punctures and cuts. Durable carcass structure improves longevity. Ensures high performance with its Low Section Height profile design. Delivers high flotation capability thanks to its wide tread design. Special carcass design supports heavy load capacity.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
10.0/75-15.3	12PR	TL	126/A8



TA 130 AGROPER

R-1W Harvester tire with aramid belted structure.

Aramid belt technology provides extra protection against stubble damage and ground impacts compared to steel and fabric alternatives. Reinforced bead structure ensures long life by improving the tire's endurance. Special tread design enables exceptional traction and better handling on the field. Wider footprint and optimized lug angle minimize soil compaction and avoid crop damage. Perfect performance under heavy loads with lower pressure compared to traditional radial tire construction. Elastic structure absorbs impacts and yields better flotation. Special tread compound offers high resistance against punctures.



TYRE SIZE	TT/TL	LOAD/SPEED INDEX
620/75 R26 (23.1 R26)*	TL	166/A8 166/B
620/75 R26 (23.1 R26)	TL	166/A8 166/B
620/75 R30 (23.1 R30)*	TL	169/A8/B
620/75 R30 (23.1 R30)	TL	169/A8/B
650/75 R32 (24.5 R32)*	TL	172/A8 172/B
650/75 R32 (24.5 R32)	TL	172/A8 72/B
800/65 R32 (30.5 R32)*	TL	178/A8 178/B
800/65 R32 (30.5 R32)	TL	178/A8 178/B

* ARAMID BELTED



PB 140 AGROPER

Modern radial harvester tire.

Offers outstanding traction on hard and soft terrains. Low rolling resistance feature improves efficiency in fuel consumption. Strong construction not only improves the tire's endurance, but also provides excellent performance. Offers high load capacity and minimum soil compaction. Special tread compound extends service life regardless of the softness or hardness of the ground.



TYRE SIZE	TT/TL	LOAD/SPEED INDEX
400/70 R20	TL	158/A8 146/A8



UN 9

Harvester rear and trailer tire.

Stable central tread section with open shoulder design enhances comfort and improves longevity. Low rolling resistance leads to maximum efficiency in fuel consumption. Strong sidewall construction and durable bead structure provides excellent protection against all kinds of damage. Offers excellent flotation and self-cleaning features.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
16.0/70-20	14PR	TL	154/A8 142/A8
400/70-20	14PR	TL	154/A8 142/A8



BD 60

Harvester tire.

Offers maximum cost efficiency in terms of both field and road performance. Suitable for heavy duty operations without causing any damage to the crops. Offers outstanding comfort and excellent traction throughout its service life thanks to its aggressive lug design. Special tread compound and strong durable carcass structure provide high resistance against cuts and wears. Unique lug geometry keeps the tread pattern free from mud.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
18.4/15-30	16PR	TT	153/A6



BD 65

Harvester tire.

Strong carcass structure supports high load capacity. Unique lug design and geometry offer outstanding traction and self-cleaning features. Strong durable carcass structure and special tread compound improve resistance against cuts and wears.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
23.1-26	12PR	TT	153/A6
23.1-26	14PR	TL	156/A6
23.1-26	18PR	TL	162/A6
23.1-30	14PR	TL	154/A6
23.1-30	12PR	TT	151/A6
23.1-30	18PR	TL	160/A6
20.8-38	14PR	TT	159/A6
20.8-38	14PR	TL	159/A6



TA 330

R1 tire designed for harvester applications.

Specially designed tread pattern provides superior traction with minimum soil compaction without causing any damage on the crops. Optimum lug frequency reduces vibration. Specially developed tread compound and lug geometry offer high resistance against lug fatigue and tread wear. Reinforced sidewalls enhance durability against cuts and impacts. Offers high load capacity.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
30.5L-32	18PR	TL	170/A6



UN 1 (5 RIB)

Modern harvester tire.

Demonstrates low dynamic rotating resistance thanks to its 5 Rib design. Suitable for short period transport and field use. Wide tread contact area prevents slides to sides and sinking into the soil. Special tread design and structure ensure high resistance against cuts and wears.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
12.5/80-15.3	12PR	TL	139/A8
12.5/80-15.3	16PR	TL	144/A8



IMF 18

General purpose flotation tire

Non-aggressive pattern is designed to ensure perfect balance with excellent grip on even the softest terrains and offer larger footprint to minimize soil compaction. Strong tread and shoulder structure enable high load capacity. Special sidewall compound protects the tire by effectively absorbing side impacts.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
12.5/80-15.3	16PR	TL	144/A8
12.5/80-15.3 RF	12PR	TL	141/A8
400/60-15.5	14PR	TL	145/A8
400/60-15.5	16PR	TL	153/149/A6
400/60-15.5	18PR	TL	155/151/A6
500/60-22.5	16PR	TL	163/A8 159/B
550/60-22.5	16PR	TL	167/A8 163/B
600/50-22.5	16PR	TL	165/A8 161/B

RF: REINFORCED



IMT 18

General purpose forestry tire.

Non-aggressive pattern is designed to ensure perfect balance with excellent grip on even the softest terrains and offer larger footprint which to minimize soil compaction and protect the crops. Reinforced tread and shoulder compound along with durable carcass structure enable high load capacity and improve durability for tough forest conditions. Special sidewall compound protects the tire by effectively absorbing side impacts.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
400/60-15.5	18PR	TL	155/151/A6
500/60-22.5	16PR	TL	163/A8 159/B 151/A8 148/B
550/60-22.5	16PR	TL	167/A8 163/B 154/A8 150/B
600/50-22.5	16PR	TL	165/A8 161/B 153/A8 149/B



IMT 08

General purpose forestry tire.

Absorbs side impacts with its special sidewall compound and grips the soil perfectly, preventing slides to sides. Non-aggressive pattern is designed to ensure perfect balance with excellent grip on even the softest terrains and offer larger footprint to minimize soil compaction. Strong tread and shoulder structure enable high load capacity. Reinforced sidewall compound improves resistance against side impacts.



TYRE SIZE	PR	TT/TL	LOAD/SPEED INDEX
500/60-22.5	16PR	TL	159/147/A8
550/60-22.5	16PR	TL	167/155/A8
600/50-22.5	16PR	TL	156/144/A8



Petlas Agricultural Tires are characterized by quality workmanship, leading edge technology, unique tread design and excellent performance, offering a mix of quality and value.

Our success depends on exceeding the expectations of our customers and standing behind everything we do.

Our aim is to build long term relationships with our customers by providing excellent service, quality and delivering our promises.



2022 EDITION



petlas

Headquarters - Factory

Petlas Tire Industry and Trade
Kindam Mahallesi Ankara - Kayseri Caddesi
No: 2/1 Kırşehir / TÜRKİYE
T: +90 386 252 65 50 • F: +90 386 252 65 70

Int. Sales & Marketing

Petlas Tire Industry and Trade Ako Kule
Söğütözü Mh. 2178. Cd. No: 6
06530 Ankara/TÜRKİYE
T. +90 312 309 30 30 • F: +90 312 309 22 66

Petlas Tire USA

1111 E. Lincolnway STE 205
Cheyenne, WY 82001 USA

www.petlas.com

Made in TÜRKİYE